## LIMITED FINISHING PREP STATION



A premium solution for prepping and painting vehicles, RTT's Limited Finishing Prep Station draws fresh air from the cleaner upper levels of the shop through a pressurization fan. The air is forced down in the prep station through a filter bank located in the ceiling near the entry. Keeping your shop clean, the air is drawn through the prep station work area into a filtered exhaust plenum at the opposite end and exhausted out to the atmosphere through the exhaust fan and stack. This design allows for the easy addition of a heated air makeup unit.



#### **Features**

- Hanging intake plenum and exhaust wall plenum are fabricated with 18-guage galvanized steel panels.
- RTT Limited finishing prep stations ship with bright, even illumination from four-tube, 48" long, 32 watt, fluorescent light fixtures. RTT light fixtures are ETL listed (Class 1 Division 2, Group A, B, C, D and Class 2 division 2, Group F and G.) and are supplied with a multi-voltage ballast to accept any voltage between 110vac and 277vac. Bulbs are pre-installed at the factory and tested prior to shipment.
- One 18" diameter efficient tubeaxial fan with a 1 ½ HP, three-phase motor.
- Supporting accessories panels, assembly hardware, filters, and exhaust fan and stack included.
- RTT's Limited finishing prep stations meet and/or exceed quality performance standards and all applicable OSHA and NFPA regulations.



RTT Limited Finishing Prep Stations are a convenient way to prep parts with easy slide curtain.

#### **Options**

- Goff™ Curtain Walls optional for closing of painting area (installed height is required).
- Control panel and other electrical components can be purchased separately.
- · Heated air makeup unit.

# LIMITED FINISHING PREP STATION



### **Selecting a Booth Size**

RTT can design and build booths in a variety of sizes and configurations. Although our team can engineer custom sizes to fit your needs, below are standard sizes that are pre-engineered and available for quick shipment.

| Model Number      | Interior Dimensions |        |        | Exterior Dimensions |        |        |             |               | Fan Spec. |       | Filters |      |
|-------------------|---------------------|--------|--------|---------------------|--------|--------|-------------|---------------|-----------|-------|---------|------|
|                   | Width               | Height | Length | Width               | Height | Length | Qty. Lights | Air Flow SCFM | Dia.      | HP    | Int.    | Exh. |
| EPS-14-10-24-P-SB | 14'-0"              | 10'-0" | 24'-0" | 14'-4"              | 12'-2" | 26'-6" | 8           | 5,000         | (2)18"    | 1.5HP | 12      | 12   |
|                   | Α                   | В      | С      |                     |        |        |             |               |           |       |         |      |



